

TECHNICAL DATA
RR ENDURO 125 4T LC

CHASSIS

Frame	steel double cradle frame
Wheel base	1435 mm
Max length	2145 mm
Max width	830 mm
Max height	1220 mm
Seat height	920 mm
Ground clearance	330 mm
Footrest height	400 mm
Dry weight	98 kg - front. 47,6 ; rear. 50,4
Fuel tank capacity	7,5 l.
Reserve	1,5 l.
Front suspension	USD Hydraulic fork ø41 mm
Rear suspension	Monoshock with progressive compound lever
Shock absorber stroke	131 mm
Front wheel travel	265 mm
Rear wheel travel	270 mm
Front brake	disc ø260 mm with CBS
Rear brake	disc ø220 mm
Front rim	21 x 1,6 - 36 holes
Rear rim	18 x 1,85 - 36 holes
Front tyre	90/90-21
Rear tyre	120/90-18

ENGINE

Type	Single-cylinder, 4-stroke, liquid cooled
Bore	52,0 mm
Stroke	58,7 mm
Displacement	124,66 cc
Compression ratio	11,2:1
Ignition	Electronic 150W-14v
Spark plug	NGK R MR8E-9
Lubrication	Forced with pump
Feeding	Unleaded gasoline
Injection	Mikuni
Clutch	Wet antihopping multi-disc clutch
Transmission	6 speed
Secondary trasmission	Z. 14/63
Engine oil	SAE 15W/50
Consumption l/100 km	2,0
Emission Co2 [g/km]	46,0